



**TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE**

**Challenges in continuous monitoring of  
transformer insulation**

**Wojciech Koltunowicz**  
**OMICRON electronics GmbH**

Wojciech Koltunowicz is with OMICRON Energy Solutions GmbH, Berlin, Germany, where he is involved in monitoring of HV equipment, leading group of Experts in Diagnostics and Monitoring Services. From 1987 to 2007 he was with CESI, Italy, where he was mainly involved in HV testing and diagnostics of HV equipment.

He received M.Sc., PhD and Dr.habil. degrees in electrical engineering from the Warsaw University of Technology in 1980, 1985 and 2004, respectively.

He is secretary of CIGRE Advisory Group D1.03 "Insulating Gases", WG D1.25 and D1.37. He is member of CIGRE AG D1.02 "High Voltage and High Current Test and Measuring Technique and Diagnostic" and WG D1.51. He is also member of IEC TC42 WG14. He is author of dozens of international reports.





**TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE**

**Challenges in continuous monitoring of  
transformer insulation**




**Challenges in continuous monitoring of transformer insulation**

**Laurentiu-Viorel BADICU**  
OMICRON Energy Solutions GmbH, Berlin, Germany




**Failure statistics of power transformers**




Patrick Picher, Hydro-Québec IREQ, and Claude Rajotte, Condition Monitoring of Aging Transformers, Hydro-Québec TransÉnergie T&D World Magazine

**Relative Annual Transformer Failure Risk  
No Maintenance**



John E. Skog, Business Case for Transformer On-line Monitoring EPRI Diagnostic Conference July 2006



S. Tenbohlen, F. Vahidi, P.Mueller, J. Gebauer, M. Krueger, Zuverlässigkeitsbewertung von Leistungstransformatoren, Stuttgarter Hochspannungssymposium, 2012





## Challenges in continuous monitoring of transformer insulation

### Content

- > Absolute measurements of bushing capacitance and dissipation factor
- > Reduction/rejection of high level interferences and sensitive PD detection
- > Case study 1: Large distribution transformer (66/22 kV)
- > Case study 2: Power transformer (230/115 kV)



©OMICRON

PAGE 3



### Case study 1: Large distribution transformer 66/22 kV

Winchelsea substation, Victoria, Australia



©OMICRON

PAGE 4





## Challenges in continuous monitoring of transformer insulation

### Case study 1: Large distribution transformer

#### Background

- Distribution transformer: 5/7MVA ONAN/ONAF 66/22kV, OIP bushing
- Constructed in **1998**, no indications of any problem
- Relocated in **2007**, not heavily loaded
- **Feb. 2010** annual DGA indicated 5400 ppm of H<sub>2</sub>
- In **2010** the oil was refurbished and on-line DGA monitoring was installed
- High concentration of H<sub>2</sub> remained




©OMICRON

PAGE 5



### Case study 1: Large distribution transformer

#### On-line DGA report



- H<sub>2</sub> and CH<sub>4</sub> steady increase → oil decomposition under ongoing PD
- CH<sub>4</sub> and C<sub>2</sub>H<sub>6</sub> → extreme overheating of the mineral oil and adjacent metals
- Low concentration of CO → no paper insulated parts involved



©OMICRON

PAGE 6





## Challenges in continuous monitoring of transformer insulation

### Case study 1: Large distribution transformer

#### Lab DGA analysis

Gas Analysis	08/03/2013	ppm/day
Sample No	6838085	
Fluid Temp C	41	
Hydrogen (H <sub>2</sub> )	4300	88.68 Very High ++
Methane (CH <sub>4</sub> )	600	4.47 High +
Ethane (C <sub>2</sub> H <sub>6</sub> )	220	1.32 Abnormal +
Ethylene (C <sub>2</sub> H <sub>4</sub> )	1	0.03
Acetylene (C <sub>2</sub> H <sub>2</sub> )	<1	0.00
Carbon Monoxide (CO)	150	1.82
Carbon Dioxide (CO <sub>2</sub> )	1200	6.05
Oxygen (O <sub>2</sub> )	880	
Nitrogen (N <sub>2</sub> )	22000	
TDCG (ppm)	5271	96.32 High ++
Equivalent TCG (%)	25.46	
Total Gas (%)	29351.000	
CO <sub>2</sub> /CO	8.00	
O <sub>2</sub> /N <sub>2</sub>	0.04	
Equipment Condition	4	




©OMICRON

PAGE 7



### Case study 1: Large distribution transformer


#### Parameters continuously monitored



©OMICRON

PAGE 8






## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Case study 1: Large distribution transformer

#### Absolute and relative C/DF measurements




©OMICRON

PAGE 9



### Case study 1: Large distribution transformer

#### Absolute C/DF measurements



- Daily changes of the system voltages do not affect the sensitivity
- Highest sensitivity is achieved
- A group of instrument transformers has to be available nearby the transformer



©OMICRON

PAGE 10





TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE


# Challenges in continuous monitoring of transformer insulation

## Case study 1: Large distribution transformer

### PD detection methods

**Electrical:**  
Conventional (according to IEC60270)  
HF/VHF/UHF

**Nonelectrical:**  
Acoustic  
Optical  
Chemical





©OMICRON

PAGE 11



## Case study 1: Large distribution transformer

### PD Measurements with Conventional and UHF Method



Example of PRPD pattern for PD defect.



©OMICRON

PAGE 12







## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Case study 1: Large distribution transformer

#### Installation and commissioning



©OMICRON


PAGE 13



### Monitoring System Components

#### Bushing tap adapters and coupling units

- Synchronously captures signals for
  - Capacitance, DF/PF
  - Transient over-voltages
  - Partial discharge
- Multiple redundant high-voltage protections
- Built-in temperature sensor
  - For temperature compensation of measured values
- IP66, -40°C...+90°C ambient temperature



Coupling unit with bushing tap adapter



©OMICRON

PAGE 14










## Challenges in continuous monitoring of transformer insulation

### Monitoring System Components

#### UHF sensor

- UHF sensor detect PD signals inside the transformer tank
- Sensor (antenna) is connected to signal converter
- Sensor is mounted at oil drain valve (or at hatch)



Drain valve sensor & converter



© OMICRON


PAGE 15



### Monitoring System Components

#### Transformer acquisition unit

- 4-channel, simultaneous acquisition of data from the bushing tap adapters and UHF sensor
- Advanced signal processing for capacitance, DF/ PF, transient over-voltages and PD calculation
- 10 analog inputs for additional measurements
  - Humidity
  - Ambient temperature
  - Optional measurements, e.g. oil pressure
- Fiber-optic communication to central computer
- IP65 enclosure, -33°C...+55°C ambient temp.



Acquisition unit



© OMICRON

PAGE 16





## Challenges in continuous monitoring of transformer insulation

### Monitoring System Components

#### Central computer and monitoring software

- State-of-the art database system for long-term data storage and retrieval
- Web-based data access & visualization
- Different user roles/logins:
  - Operator:
    - Overview of full system setup
    - View all data with free configurable charts and diagrams
    - Confirm warnings and alarms
  - Administrator: As operator, plus
    - Configuration of all monitoring parameters
    - Set and change warning and alarm rules




© OMICRON

PAGE 17



### Monitoring Software - GUI



© OMICRON

PAGE 18





# Challenges in continuous monitoring of transformer insulation

## Commissioning

Standards and recommendations regarding DF

Type	RIP	OIP	RBP
Main insulation	Resin impregnated paper	Oil impregnated paper	Resin bonded paper
DF / tan delta (20°C, IEC60137)	< 0.7 %	< 0.7 %	< 1.5 %
PF cos phi (20°C, IEEE C57.19.01)	< 0.85 %	< 0.5 %	< 2 %
Typical new values	0.3-0.4 %	0.2-0.4 %	0.5-0.6 %
PD (IEC60137) at $U_m$ $1.5 U_m / \sqrt{3}$ $1.05 U_m / \sqrt{3}$	< 10 pC < 5 pC < 5 pC	< 10 pC < 5 pC < 5 pC	< 300 pC



©OMICRON

PAGE 19




## Analysis of the results

Temperature correction of DF

$$\tan\delta \downarrow 20^\circ = c_{Mat}(\vartheta) * \tan\delta \downarrow B$$

where:

- $\vartheta$  is the bushing temperature
- $c_{Mat}$  is a correction factor depending on the insulation system of the bushing (OIP, RIP, RBP-Drysonic and RBP-Superresocel)



Temperature dependence of the dissipation factor [Karl Frey, Micafil]



©OMICRON

PAGE 20







## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Analysis of the results

#### Capacitive bushing design

Voltage [kV]	No. of layers	% change
123	14	7.1
245	30	3.3
420	40	2.5
550	55	1.8







© OMICRON

PAGE 21



### Analysis of the results

#### Absolute values of capacitance and DF



© OMICRON

PAGE 22






## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE


# Challenges in continuous monitoring of transformer insulation

### Analysis of the results


#### Conventional PD measurements



measuring frequency according  
to IEC 60270 (below 1MHz)



measuring frequency outside  
IEC 60270 recommendation (@ 3MHz)




©OMICRON

PAGE 26



### Analysis of the results

#### Partial discharges analysis using the conventional method



©OMICRON

PAGE 24







## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Analysis of the results

#### Partial discharges analysis – electrical method



Acoustic PD localization  
measurements  
are recommended





©OMICRON

PAGE 25



### Analysis of the results

#### Partial discharges analysis – UHF method



©OMICRON

PAGE 26






TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE

# Challenges in continuous monitoring of transformer insulation

## Analysis of the results

### Rejection of disturbances by UHF gating




©OMICRON

PAGE 27



## Analysis of the results

### Acoustic measurements triggered by the UHF signal



©OMICRON

PAGE 31






TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE

# Challenges in continuous monitoring of transformer insulation

## Analysis of the results

### Transient Over-voltages

20 transient over-voltages were recorded → highest amplitude 1.77 p.u.



©OMICRON

PAGE 29



## Case study 2: Power transformer 230/115 kV



©OMICRON

PAGE 30







## Challenges in continuous monitoring of transformer insulation

### Case study 2: Power transformer 230/115 kV

#### Background

- 130/130/100 MVA – 230/115/48 kV – 1973
- monitoring system installed on 230 kV side in 2013
- bushing of **phase A** was replaced in 2010
- RBP bushings
- absolute measurements of C/DF are performed
- reference signal taken from VTs
- continuous increase in H<sub>2</sub> concentration from March 2014 to June 2014




© OMICRON

PAGE 31



### Case study 2: Power transformer 230/115 kV

#### Monitoring system installation



© OMICRON

PAGE 39

OMICRON



## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Case study 2: Power transformer 230/115 kV

#### Absolute values of capacitance and DF



Capacitance variation and dissipation factor limits for RBP bushings

$U_N$ [kV]	$\tan \delta$ [%]	$\Delta C$ [%]
123	2.0	20
245	1.5	15
420	1.0	10

S. Tenbohlen et al., "Enhanced Diagnosis of Power Transformers using On- and Off-line Methods: Results, Examples and Future Trends", CIGRE Session 2000, paper 12-204, Paris, 2000.




©OMICRON

PAGE 33




### Case study 2: Power transformer 230/115 kV

#### PD trend from electrical method



#### PD trend from UHF method



©OMICRON

PAGE 41








## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Case study 2: Power transformer 230/115 kV

Partial discharges analysis – electrical method – February 2014






© OMICRON

PAGE 42




### Case study 2: Power transformer 230/115 kV


PD – DGA correlation



5<sup>th</sup> of February



16<sup>th</sup> of April



25<sup>th</sup> of June



© OMICRON

PAGE 43






## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation

### Case study 2: Power transformer 230/115 kV

#### Partial discharges analysis – UHF method




©OMICRON

PAGE 44



### Case study 2: Power transformer 230/115 kV

#### Acoustic PD measurement



©OMICRON

PAGE 51






## TRANSFORMER-LIFE-MANAGEMENT CONFERENCE

# Challenges in continuous monitoring of transformer insulation


### Acoustic PD measurement

#### 1st sensor position



### Acoustic PD measurement

#### 2nd sensor position





TRANSFORMER-LIFE-MANAGEMENT  
CONFERENCE

# Challenges in continuous monitoring of transformer insulation

## Case study 2: Internal inspection



41



## Case study 2: Internal inspection



42





## Challenges in continuous monitoring of transformer insulation

### Conclusions

The monitoring system provider needs to overcome a lot of challenges to achieve:

- **High accuracy of C and DF monitoring values**

It can be achieved by performing absolute measurements with reference signal taken from VTs.

- **High sensitivity of PD measurement:**

Combining of conventional and UHF PD detection methods.

Using advanced SW features – multi-channel and multi-spectral technique for multiple PD source separation and noise elimination.



©OMICRON

PAGE 54



**Thank you very much for your attention!**



©OMICRON

19 Oktober 2014